

12/12/84

ASHFORD HANDICRAFTS LTD

P.O. BOX 180, ASHBURTON, NEW ZEALAND. FACTORY: 415 - 429 WEST STREET, ASHBURTON,
PHONES FACTORY & OFFICE 89-087, MILL HOUSE RETAIL SHOP 89-085.
TELEX No. AR 4763 PREFIX ASHFORD. CABLES: ASHFORDS, ASHBURTON.

The ASHFORD Rug Frame

SEALING THE TIMBER OF YOUR RUG FRAME:

Ashford Rug Frames are made from kiln dried timber but due to possible climatic changes it is important that on arrival the timber surface is sealed. This improves its appearance and protects the wood.

First use the garnet paper to smooth the wood, then brush off dust. Then apply a sealer before assembling.

Silver Beech has a delightful variety of colours, but if desired a medium to dark stain will cover any differences. We recommend the following sealers:

- Any clear vegetable oil may be brushed on to the wood to give a natural finish. Repeat this process as required to maintain colour.
- A french polish may be applied with brush or pad.
- Any stain followed by several coats of polyurethane or lacquer.
- Consult your paint dealer for further information or alternatives.

LIST OF PARTS:

- | | |
|---------------------|---------------|
| a) Feet (2) | b) Legs (2) |
| c) Toprail | d) Braces (2) |
| e) Kneebars | f) Arms (2) |
| g) Rebated top rail | |
- plus 1 packet of hardware

ASSEMBLY INSTRUCTIONS:

- Secure feet A to legs B with Round Head screws.
- Secure top rail C to legs B with Countersunk screws.
- Locate braces D in position to legs and then secure to top rail with screws.
- Fix kneebars E to arms F with countersunk screws and attach them to legs B with bolts.
- Now place the rebated top rail G in place and secure with bolts

Your rug frame is now ready for use. Hang unworked canvas over top rail and secure with rebated rail. Swing kneebars out into position and tighten wing nut. Work on your rug between knee rail and top rail.

MANUFACTURED BY: Ashford Handicrafts Ltd
Ashburton
New Zealand.

